

Capítulo 7

Referências bibliográficas

- [1] AHMADIAN, M. (2003). Laboratory evaluation of heavy truck dynamics: are the test results useful?. *International Truck & Bus Meeting and Exposition*, SAE paper 2003-01-3395
- [2] ANDERSON, D. et al (2001). Development of a multi-body dynamic model of a tractor-semitrailer for ride quality prediction. SAE paper 2001-01-2764
- [3] BARAK, P. (1991). Magic numbers in design of suspensions for passenger cars. *Passenger Car Meeting and Exposition*. Nashville, Sep.16-19, SAE paper 911921
- [4] BASTOW, D. (1976). Aspects of car rear suspension. *Proceedings I.Mech.E.*, Automobile Division, vol.190 53/76
- [5] BASTOW, D. (1990). *Car suspension and handling*. London: Pentech Press
- [6] BAUM, J.H.; BENNETT, J.A.; CARNE, T.G. (1977). Truck ride improvement using analytical and optimization methods. *2nd International Conference on Vehicle Structural Mechanics*, SAE paper 770609
- [7] BEST, A. (1984). Vehicle ride – stages in comprehension. *Phys.Technology*, Northern Ireland, vol.15
- [8] BIDWELL, J.B. (1970). State of the art - Vehicle control and road holding. *International Automobile Safety Conference*, Detroit, Michigan, SAE paper 700366
- [9] BIXEL, R.A.; et.al. (1996). Sprung/Unsprung mass properties determination without vehicle disassembly. SAE paper 960183
- [10] BROULHIET, GEORGES (1933). Independent wheel suspension. *SAE Transactions*, vol.28

- [11] BROWN, R.W. (1928). The measurement of riding-qualities. *SAE Transactions*, vol.23
- [12] BROWN, R.W. (1932). The tire factor in automobile riding-quality. *SAE Transactions*, vol.27
- [13] BRUNS, H.J.; RÖNITZ, R. (1971). Optimizing ride comfort. *Automobile Engineer* 61, No 3
- [14] BUTKUNAS, A.A. (1966). Power spectral density and ride evaluation. SAE paper 660138
- [15] CAMPBELL, C. (1981). *New directions in suspension design*. Cambridge: Robert Bentley
- [16] CHENCHANNA, P. (1969). Ride-comfort and road holding. *Automobile Engineering*, vol.59, p.296-300
- [17] COSTA NETO, A. (2000). *Dinâmica veicular*. São Carlos: SAE Brasil
- [18] COX, H.L. (1955). The riding qualities of wheeled vehicles. *Proceeding of I.Mech.E.*, Automobile Division, n.10
- [19] CRAIG Jr., R.R. (1981). *Structural dynamics an introduction to computer methods*, John Wiley & Sons, New York
- [20] CROLLA, D.A.; KING, R.P. (1999). Olley's "flat ride" revisited. *Vehicle System Dynamics*, 33, p.762-774
- [21] CROSBY, M.J.; ALLEN, R.E. (1974). Cab isolation and ride quality. SAE paper 740294, Detroit
- [22] DAHLBERG, T. (1978). Ride comfort and road holding of a 2-DOF vehicle traveling on a randomly profiled road. *Journal of Sound and Vibration*
- [23] DEN HARTOG, J.P. (1984). *Mechanical vibrations*. New York: Dover Publications

- [24] ELLIS, J.R. (1962). Experimental confirmation of ride theory. *Proceedings of a Symposium on Vehicle Ride*, Advanced School of Automobile Engineering, Cranfield
- [25] FOSTER, A.W. (1978). A heavy truck cab suspension for improved ride. SAE paper 780408, Congress and Exposition, Cobo Hall, Detroit
- [26] GILLESPIE, T.D. (1985). *Heavy truck ride*. Michigan: Society of Automotive Engineers Inc
- [27] GILLESPIE, T.D. (1992). *Fundamentals of vehicle dynamics*. Michigan: Society of Automotive Engineers Inc
- [28] GUEST, J.J. (1925). The main free vibrations of an autocar. *Proceedings of the Institution of Automobile Engineers*, vol.20
- [29] HAMANO, T.; et.al. (1995). Characteristic of hysteresis curve of the leaf spring., SAE paper 958481
- [30] HERRMANN, J.G.; NOGUEIRA, F.; SIQUEIRA, L.P. et al (2002). Tractor air suspension design and tuning. *Truck Vehicle Dynamics & Suspension* (SP-1728), SAE paper 2002-01-3041
- [31] HU, H.X. (1993). Experimental validation of a half-vehicle suspension model. SAE paper 931966
- [32] INMAN, D.J. (2001). *Engineering vibration*. New Jersey: Prentice Hall
- [33] INOH, TAKESHI; AISAKA, MASAHARU (1973). Tuning techniques for controlling heavy-duty truck shake vertical, torsional, and lateral. *Combined Commercial Vehicle Engineering & Operations and Powertrain Meeting*, Chicago, SAE paper 730650, June 18-22
- [34] JACKSON, G.W. (1959). Fundamentals of the direct acting shock absorber. *SAE National Passenger Car, Body and Materials Meeting*, Detroit, March 16-18, SAE paper 590089

- [35] JANEWAY, R.N. (1958). A better truck ride for driver and cargo – problems and practical solutions. *SAE Annual Meeting*, 148 pages, SAE paper 580269
- [36] JANEWAY, R.N. (1965). Chassis effects on tandem ride – a summary., SAE paper 650183
- [37] JANKOWSKI, K.P. (1998). Analytical investigation of light truck low frequency vibration issues. *International Congress and Exposition*, Detroit, Feb.23-26, SAE paper 981170
- [38] KIM, M.G.; HYUN, C.H.; JEONG, H. (1994). The effects of vehicle velocity and engine mount stiffness on ride comfort. *International Congress & Exposition*, SAE paper 941045
- [39] KINCHIN, J.W.; STOCK, C.R. (1951). Shock absorbers. *I.Mech.E.*, Automobile Division Proceedings
- [40] KOHR, R.H. (1961). Analysis and simulation of automobile ride. SAE paper 610011
- [41] KURT, O.E. (1933). An analysis of tires and wheels as causes of tramp. *SAE Transactions*, vol.28
- [42] LANCHESTER, F.W. (1907). Some problems peculiar to the design of the automobile. *Proceedings of the Institution of Automobile Engineers*, vol.2, p.197-287
- [43] LEDESMA, R. (2002). Ride performance comparison of trailer suspension systems using computational methods. *International Truck & Bus Meeting and Exposition*, SAE paper 2002-01-3103
- [44] Le FREVE, W.F. (1965). The highway truck ride problem. SAE paper 650177
- [45] LITCHFIELD, P.W. (1913). Pneumatic tires. *SAE Transactions*, vol.8
- [46] MARTZ, J.W. et al (1979). Four steps for vehicle ride improvement., *Automotive Engineering Congress and Exposition*, SAE paper 790219, Detroit

- [47] MEIROVITCH, L. (1975). *Elements of vibration analysis*. New York: McGraw-Hill
- [48] MOSS, F.A. (1931). Measurement of comfort in automobile riding. *SAE Transactions*, vol.25-26
- [49] NORTON, R.L. (1992). *Design of machinery*. London: McGraw-Hill
- [50] NUMAZAKI, I.; YAMAMOTO, E.; HAMANO, T. (1991). Analysis on the Hysteresis loop of the leaf spring. *International Truck & Bus Meeting and Exposition*, Chicago, SAE paper 912715
- [51] OHTA, M.; NISHIDA, T.; SUZUKI, K.; UEHARA, M. (1990). The influence of tire deformation on ride comfort of a truck. SAE paper 902268
- [52] OLLEY, M. (1921). European and American automobile practice compared. *Transactions of the Society of Automotive Engineers*, vol.16
- [53] OLLEY, M. (1934). Independent wheel suspension – its whys and wherefores. *SAE Transactions*, vol.34, n.3
- [54] OLLEY, M. (1943). Notes on light motor cars, SAE paper 430083
- [55] OLLEY, M. (1944). Speculations on post war cars, SAE paper 440052
- [56] OLLEY, M. (1946). Road manners of the modern car. *Proceedings of the Institution of Automobile Engineers*, vol.51
- [57] OLLEY, M. (1955). Report on suspensions for commercial vehicles. SAE paper 550125
- [58] PERSEGUIM, O.T.; COSTA NETO, A.; FOGAÇA, M.A.; et. al. (2000). Comfort and vibration of a tractor and trailer combination using simulation and experimental approaches. *Truck and Bus Meeting and Exposition. Ergonomics, Work Station and Driver Issues – SP-1570*, SAE Paper 2000-01-3517

- [59] PERSEGUIM, O.T.; PERES, E.; FERNANDES, C.G. (2003). Pickups vehicle dynamics: ride and skate. *Congresso SAE Brasil 2003*, São Paulo, SAE paper 2003-01-3588
- [60] PERSEGUIM, O.T.; KNOLL, P.H. et al (2004). Ride básico de um veículo cavalo carreta. *Colloquium de Suspensões SAE*, Caxias do Sul
- [61] The effects of loaded radial runout on tire roughness and shake, SAE paper 610545
- [62] POLAK, P.; BURTON, R.T. (1971). Improving suspension damping. *Journal Automotive Engineering*, p.13-17
- [63] POLHEMUS, V.D. (1950). Secondary vibrations in rear suspension – part II. *SAE journal*, July
- [64] PURDY, J.F.; DAY, R.B. (1927). A method of measuring the cushioning quality of tires. *SAE Transactions*, vol.22
- [65] RIBARITS, J.I.; AURELL, J.; ANDERSERS, E. (1978). Ride comfort aspects of heavy truck design. *Truck Meeting*, Dearborn, SAE paper 781067
- [66] RIDER, K.A. et.al (2003). A pilot study of the effects of vertical ride motion on reach kinematics. *Reprinted from Human Factors in Driving, Seating & Vision*, 2003 SAE World Congress, Detroit, March 3-6, SAE paper 2003-01-0589
- [67] ROWELL, H.S. (1922). Principles of vehicle suspension. *Proceedings of the Institution of Automobile Engineers*, vol.17
- [68] RYBA, D. (1973). Possible improvements in ride comfort. *Vehicle System Dynamics 2*
- [69] SANCHEZ, J.P.A. (1997). *Estudo comparativo de desempenho entre suspensões passiva, semi-ativa e totalmente ativa utilizando modelo completo de veículo*. Dissertação (Mestrado) - Escola de Engenharia de São Carlos, Universidade de São Paulo, São Carlos 1997
- [70] SCHILLING, R. (1961). Ride requirements. SAE paper 610052

- [71] SHARP, A. (1909). Pneumatic springs for road vehicles. *Proceedings of the Institution of Automobile Engineers*, vol.4
- [72] SHARP, R.S.; PILBEAM, C. (1993). Achievability and value of passive suspension designs for minimum pitch response. *Proceedings I.Mech.E.*, Conference on Vehicle Ride and Handling, p.243-259
- [73] SUN, T.; ZHANG, Y.; BARAK, P. (2002). 4-DOF vehicle ride model. *Proceedings of the 2002 SAE Automotive Dynamics and Stability Conference and Exposition*, Detroit, May 7-9, SAE paper 2002-01-1580
- [74] THOMPSON, A.G. (1969). Optimum damping in a randomly excited non-linear suspension. *Proceedings I.Mech.E.*, vol.184, n.2A, p.169-178
- [75] VU, H.V.; ESFANDIARI, R.S. (1998). *Dynamic systems modeling and analysis*. New York: McGraw-Hill
- [76] WARD, C. H. (2002). The application of a new cab mounting to address cab shake on the 2003 Chevrolet Kodiak and GMC Topkick. *International Truck and Bus Meeting and Exposition*, Detroit, Nov.18-20, SAE paper 2002-01-3102